


79460200	<b>DATA SHEET</b>	
Valid from: 14.11.2025	<b>EPIC® H-A 10 TGH/TSH</b>	

## Description

- The standard for housings. Large selection of different inserts.
- Easy-to-grip, user-friendly design makes it easy to plug and unplug the connector.

## General Characteristics

Series	H-A 10
Locking	pins for single lever
Cable entry	top / side
Protection (DIN EN 60529)	IP 65 (latched)
Protection (NEMA 250, UL50E)	4, 12 (latched)
Temperature Range	-40°C to +125°C

## Materials and Surfaces

Housing	aluminium alloy, powder-coated, grey
Gasket	NBR

## Approvals

UL-Approval, E-File-Number	E75770
----------------------------	--------

## Standard

Safety Standard	IEC 61984
-----------------	-----------

## Versions

Article number	Article description	Thread M	Cable entry
79460200	EPIC® H-A 10 TGH M20	M20x1,5	top
79460400	EPIC® H-A 10 TGH M25	M25x1,5	top
79462200	EPIC® H-A 10 TSH M20	M20x1,5	side
79462400	EPIC® H-A 10 TSH M25	M25x1,5	side




Creator: TODV1/BU EPIC Released: MAJU2/BU EPIC	Document: DB79460200EN Version: 02	Page 1 of 2
---------------------------------------------------	---------------------------------------	-------------



79460200	<b>DATA SHEET</b>	
Valid from: 14.11.2025	<b>EPIC® H-A 10 TGH/TSH</b>	

## Technical Drawings

Top cable entry



Side cable entry



Industrial machinery and plant engineering



Mechanical resistance



Robust



Waterproof



Automation

### Info

Universal, robust metal housings size H-A 10

### Application range

Plant engineering, Light & sound technology, Plastics industry

### Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Creator: TODV1/BU EPIC Released: MAJU2/BU EPIC	Document: DB79460200EN Version: 02	Page 2 of 2
---------------------------------------------------	---------------------------------------	-------------