

ECO Line I

Linear LED luminaire

IP65 | 120lm/W

100 000 h

>50 000

100% (<1s)

E

A
↑
G



4000 K

LHL020DB 20W

IP 65

IK 08

lumen
2400
Fixture

20W
LED lamp

220-240V
50/60
Hz

120°

CRI(RA)

>80

Kelvin

4000

F

Hg

PF

>0,9

4000 K

LHL040DB 40W

IP 65

IK 08

lumen
4800
Fixture

40W
LED lamp

220-240V
50/60
Hz

120°

CRI(RA)

>80

Kelvin

4000

F

Hg

PF

>0,9

4000 K

LHL060DB 60W

IP 65

IK 08

lumen
7800
Fixture

60W
LED lamp

220-240V
50/60
Hz

120°

CRI(RA)

>80

Kelvin

4000

F

Hg

PF

>0,9



Q	WATT	IP	Lumen	Beam angle	Volt	Color temperature	CRI	cosφ Power Factor	EAN	EEI	Dimensions
LHL020DB	20W	65	2400lm	120°	200-240V	4000K	>80	>0,9	---	E	630x74x62mm
LHL040DB	40W	65	4800lm	120°	200-240V	4000K	>80	>0,9	---	E	1230x74x62mm
LHL060DB	60W	65	7800lm	120°	200-240V	4000K	>80	>0,9	5901087210526	E	1530x74x62mm