

CERTIFICATE

Issued to:
Applicant:
LEDVANCE GmbH
Parkring 1-5
85748 Garching, Germany

Licensee:
LEDVANCE GmbH
Parkring 1-5
85748 Garching, Germany

Product : URBAN LANTERN
Trade name(s) : LEDVANCE
Type(s)/model(s) : URBAN LANTERN V 29W ASYM PS 822-827 IP66 BK,
URBAN LANTERN V 29W ASYM PS 822-827 IP66 GY,
URBAN LANTERN V 29W ASYM PS 830-840 IP66 BK,
URBAN LANTERN V 29W ASYM PS 830-840 IP66 GY,
URBAN LANTERN V 29W SYM PS 822-827 IP66 BK,
URBAN LANTERN V 29W SYM PS 822-827 IP66 GY,
URBAN LANTERN V 29W SYM PS 830-840 IP66 BK,
URBAN LANTERN V 29W SYM PS 830-840 IP66 GY,
URBAN LANTERN V 59W ASYM PS 822-827 IP66 BK,
URBAN LANTERN V 59W ASYM PS 822-827 IP66 GY,
URBAN LANTERN V 59W ASYM PS 830-840 IP66 BK,
URBAN LANTERN V 59W ASYM PS 830-840 IP66 GY,
URBAN LANTERN V 59W SYM PS 822-827 IP66 BK,
URBAN LANTERN V 59W SYM PS 822-827 IP66 GY,
URBAN LANTERN V 59W SYM PS 830-840 IP66 BK and
URBAN LANTERN V 59W SYM PS 830-840 IP66 GY

The product and any acceptable variation thereto as specified in the Annex to this certificate and the documents therein referred to.

DEKRA hereby declares that the above-mentioned product has been certified on the basis of:


- a type test according to EN IEC 60598-1:2021, EN IEC 60598-1:2021/A11:2022, EN 60598-2-3:2003 and EN 60598-2-3:2003/A1:2011
- an inspection of the factory location according to CENELEC Operational Document CIG 021
- a DEKRA certification agreement with the number 6057933

DEKRA hereby grants the right to use the ENEC certification mark.

The ENEC certification mark may be applied to the product as specified in this certificate for the duration and under the conditions of the ENEC certification agreement.

This certificate is issued on 3 January 2024 and expires upon withdrawal of one of the above mentioned standards.

DEKRA Certification B.V.



B.T.M. Holtus
Managing Director



K Xu
Certification Manager

© Integral publication of this certificate is allowed

ACCREDITED BY THE
DUTCH ACCREDITATION
COUNCIL



Certificate number: 31-134739

SPECIFICATION OF THE CERTIFIED PRODUCT

Product data

Product	: URBAN LANTERN
Trade name(s)	: LEDVANCE
Type(s)/model(s)	: URBAN LANTERN V 29W ASYM PS 822-827 IP66 BK, URBAN LANTERN V 29W ASYM PS 822-827 IP66 GY, URBAN LANTERN V 29W ASYM PS 830-840 IP66 BK, URBAN LANTERN V 29W ASYM PS 830-840 IP66 GY, URBAN LANTERN V 29W SYM PS 822-827 IP66 BK, URBAN LANTERN V 29W SYM PS 822-827 IP66 GY, URBAN LANTERN V 29W SYM PS 830-840 IP66 BK, URBAN LANTERN V 29W SYM PS 830-840 IP66 GY, URBAN LANTERN V 59W ASYM PS 822-827 IP66 BK, URBAN LANTERN V 59W ASYM PS 822-827 IP66 GY, URBAN LANTERN V 59W ASYM PS 830-840 IP66 BK, URBAN LANTERN V 59W ASYM PS 830-840 IP66 GY, URBAN LANTERN V 59W SYM PS 822-827 IP66 BK, URBAN LANTERN V 59W SYM PS 822-827 IP66 GY, URBAN LANTERN V 59W SYM PS 830-840 IP66 BK and URBAN LANTERN V 59W SYM PS 830-840 IP66 GY
Rated voltage	: 220-250 Vac
Rated frequency	: 50/60 Hz
Ambient temperature(ta)	: 50°C
IP code	: IP66
Classification according to type of protection against electric shock	: Class II

**Product data – type URBAN LANTERN V 29W ASYM PS 822-827 IP66 BK,
URBAN LANTERN V 29W ASYM PS 822-827 IP66 GY,
URBAN LANTERN V 29W SYM PS 822-827 IP66 BK and
URBAN LANTERN V 29W SYM PS 822-827 IP66 GY**

Input wattage (max.)	: 15 / 20 / 25 / 29 W
CCT	: 2200 K / 2700 K

**Product data – type URBAN LANTERN V 29W ASYM PS 830-840 IP66 BK,
URBAN LANTERN V 29W ASYM PS 830-840 IP66 GY,
URBAN LANTERN V 29W SYM PS 830-840 IP66 BK and
URBAN LANTERN V 29W SYM PS 830-840 IP66 GY**

Input wattage (max.)	: 15 / 20 / 25 / 29 W
CCT	: 3000 K / 4000 K

**Product data – type URBAN LANTERN V 59W ASYM PS 822-827 IP66 BK,
URBAN LANTERN V 59W ASYM PS 822-827 IP66 GY,
URBAN LANTERN V 59W SYM PS 822-827 IP66 BK and
URBAN LANTERN V 59W SYM PS 822-827 IP66 GY**

Input wattage (max.)	: 34 / 42 / 49 / 59 W
CCT	: 2200 K / 2700 K

**Product data – type URBAN LANTERN V 59W ASYM PS 830-840 IP66 BK,
URBAN LANTERN V 59W ASYM PS 830-840 IP66 GY,
URBAN LANTERN V 59W SYM PS 830-840 IP66 BK and
URBAN LANTERN V 59W SYM PS 830-840 IP66 GY**

Input wattage (max.)	: 34 / 42 / 49 / 59 W
----------------------	-----------------------

CCT : 3000 K / 4000 K

TESTS

Test requirements

EN IEC 60598-1:2021
EN IEC 60598-1:2021/A11:2022
EN 60598-2-3:2003
EN 60598-2-3:2003/A1:2011

Test result

The test results are laid down in DEKRA test file 617490600.

Additional information

The products also comply with EN 62493:2015+A1:2022

Note:

"xxxx" may after basic code, it is optional. "x" could be blank, different letter or number, to represent different customer brand or for internal IC code.

The list of components is laid down in test report 6174906.50.

Conclusion

The examination proved that all requirements were met.

Factory location

LEEDARSON LIGHTING CO., LTD.
Xingtai Industrial Zone, Economic Development Zone, Changtai County,
363900 Zhangzhou City Fujian, China